

ORDER

SL 35

Position
_____ / _____

Required delivery week: _____

1. Number of units
_____ pieces

2. Stacking
 Inside
 Outside

3. Number of panels (inside view)
 _____ left direction
 _____ right direction

4. Glass
 with: _____
 prepared for _____ mm

5. Cleaning pin
 (Installation of cleaning pin only possible with top hung systems)

6. Surface profile + panel connector
RAL _____
 or
Profile Eloxal

 + Panel connector
RAL _____

Flat handle: (standard)
 RAL 9016 9006
 9007 8077
 Special colour
 RAL _____
 (additional charge)

Client:

 Tel: _____ Fax: _____
 Contact person _____

Ref:
 Quotation number:
 Delivery address (if different to client):

7. Hardware types ATTENTION! For **parapet installations:** Handle height from frame underside _____ mm

<input type="radio"/> Flat handle on inside without lock (standard) 	<input type="radio"/> Flat handle on inside/outside without lock 	<input type="radio"/> Flat handle on inside/outside with cylinder lock
---	--	--

8. Floor track options (Examples are to be found on www.solarlux.com)

<input type="radio"/> 5-35-07-x Drainage <input type="radio"/> yes <input type="radio"/> no	<input type="radio"/> 5-35-02-x inside opening <input type="radio"/> 5-35-11-x outside opening Drainage <input type="radio"/> yes <input type="radio"/> no
<input type="radio"/> 5-50-23-x No factory installed drainage	<input type="radio"/> 5-45-43-x No factory installed drainage

9. Drawing

Elevation from inside

External frame size (width): _____ mm

External frame size (height): _____ mm

number of panels and opening direction

Plan view

Outside _____

Inside _____
 panel shown in open position (stacking position)