

ORDER

SL 80

Position
_____ / _____

Required delivery week: _____

1. Number of units
_____ pieces

2. Stacking
 Inside
 Outside

3. Number of panels (inside view)
 _____ left direction
 _____ right direction

4. Glass
 with: _____
 prepared for _____ mm

5. Surface Profile:
RAL _____
 or
Eloxal

Hinge:
 Eloxal E6EV1
 E6C34

Flat handle:
 RAL 9016 9006
 9007 8077
 Special colour
 RAL _____
 (additional charge)

Client:

 Tel: _____ Fax: _____
 Contact person _____

Ref:
 Quotation number:
 Delivery address (if different to client):

6. Hardware types ATTENTION! For **parapet installations:**
 Handle height from frame underside _____ mm

<input type="radio"/> Flat handle on inside without lock (standard) 	<input type="radio"/> Lever HEWI handle inside/outside with key cylinder (only possible on first opening swing panels) 	Note: Outside opening swing panel requires SL comfort locking
---	--	--

7. Floor track options (Examples are to be found on www.solarlux.com)

<input type="radio"/> 5-80-22-x Drainage <input type="radio"/> yes <input type="radio"/> no	<input type="radio"/> 5-80-24-x Inside opening No factory installed drainage Outside opening Drainage <input type="radio"/> yes <input type="radio"/> no
---	---

8. Drawing

Elevation from inside

Outside

Plan view _____

Inside
 panel shown in open position (stacking position)