## **ORDER**



Client: Ref: **SL 66** Quotation number: **Position** Delivery address (if different to client): Required delivery week: Fax: Tel· 1. Number of units Contact person pieces 2. Stacking 9. Hardware types ATTENTION! For parapet installations: Inside Handle height from frame underside. mm Outside  $\bigcirc$ Flat handle Lever HEWI handle Flat handle on 3. Panel indide/outside inside/outside with inside without key cylinder lock (standard) with profile O Top hung cylinder (only (only possible on possible with first opening swing O Floor mounted pair panel) panels) (standard) **10. Floor track options** (Examples are to be found on www.solarlux.com) 4. Number of panels (inside view) 5-66-06-x ○ 5-66-07-x O 5-66-12-x outside dimension \_left direction inside and outside opening inside and outside opening outside dimension right direction 5. Glass O with: . 60 66 96 O prepared for O yesOno O yesO no Drainage Drainage No factory installed drainage mm outside dimension outside dimensior O 5-71-25-x 6. Wood type O Nordic pine Spruce 78.5 153.5 66 7. Wood finish No factory installed drainage No factory installed drainage (according to SL colour chart) primed 11. Drawing **Elevation** final finish from inside External frame size (with): 8. Colour of hardware Floor track: External frame size (height) ○ E6 EV1 ○ E6 C34 number of panels and opening direction Hinge: OÉ6 EV1 Flat handle: RAL \( \) 9016 \( \) 9006 O9007 O8077 Outside in Special colour Plan view

panel shown in open position (stacking position)

33/2007 - subject to technical changes without notice

RAL

(additional charge)

Inside